TxDOT Primary Researchers

Thomas Bohuslav, P.E. *Program Coordinator (OPR)*

Dr. German Claros, P.E. *Implementation Director (ID)* **Dr. Mike Murphy, P.E** *Project Monitoring Committee*

CTR Primary Researchers

Terry Dossey Research Scientist, Principal Investigator

Dr. Seong-Min Kim *Research Associate*

Website Access & Personnel

URL: <u>http://www.utexas.edu/research/ctr/Training</u> IP: 146.6.177.170 NT Server Contact: <u>terry.dossey@mail.utexas.edu</u> Unix Server Contact: <u>lavaye@uts.cc.utexas.edu</u> IT Consultant: The Transtec Group, Austin TX Consultant Contact: <u>jasond@thetranstecgroup.com</u> All software is programmed in XML, maintained on a NT server located at CTR Red River, and accessed via a redirect through the

Texas Department of Transportation

University Unix URL above.



Rigid Pavement Design and Analysis Web-Based Training Site © 2004, *Texas Department of Transportation, All Rights Reserved*

Rigid Pavement Design and Analysis Web-Based Training Site

http://www.utexas.edu/research/ctr/training

Texas Department of Transportation, 2004

Product 5-1869-03-P8 produced under Project 5-1869-03

Performed in cooperation with the Texas Department of Transportation and the Federal Highway Administration



Overview

This website offers training for six computer programs pertaining mainly to the design and analysis of rigid pavements. The programs are: CRCP9, CRCP10, JRCP6, PavePro, RPLCCA, and TxPTS (includes ACP as an option). Each program will be discussed in the sections that follow.

For each program, you may:

- Take a series of training modules, ranging from how to input data into the program to how to interpret the output,
- Download the actual program to your PC after successfully completing the training, and
- Keep a record of where you were in the training so that you may return at a later time and resume where you left off.

System Requirements

To run the training programs, you'll need only:

- A recent version of either the MS Internet Explorer or Netscape web browser,
- An open internet connection

Online Training	create a new account and password
TxDOT 2	og in with your account
User name was not found. Please try again.	
Welcome to CTR's training site is pavement organeering software applications. If you have already created approximately below. (3) Forgot Password? No problem Otherwise, please create a new account	
Login User Name: Terry Password: Events Login	Password Problems If you have forgotten your password, it can be e-mailed to you. User Name: E-mail Password In the event that your e-mail address is no longer valid,
avill pood a uppr name and parameters the proper	please <u>contact the Web site administrator</u> to reset your password. Please include your user name in the e-mail.
'ou'll need a user name and password so the program can keep track of your progress and start up wher ou left off last time. Also, after completing a module you'll be able to download updated versions of the rograms at any time.	

TxPTS

The Texas Pavement Type Selection program allows a user to compare several paving strategies and ranks them according to their cost effectiveness. It is a similar program to the RPLCCA program discussed above, but takes fewer costs into account and thus requires fewer user inputs. The performance models used are less complicated than those included in RPLCCA, and do not address specific distresses. However, TxPTS includes flexible pavements for new construction whereas RPLCCA only allows flexible overlays over rigid pavements. Like RPLCCA, TxPTS primarily uses life cycle cost analysis to rank the various strategies under consideration.

It is recommended that the interested user take the training modules on both programs to determine which one is more appropriate for their design situation.



RPLCCA

This program is a MS Windows-based software program to perform Rigid Pavement Life Cycle Cost Analysis. The purpose of the program is to allow direct comparisons of all costs associated with several design and rehabilitation strategies over the life of the pavement, so that the most cost-effective option can be selected. The program includes performance prediction models so that the rate of distress development characteristic to each type of pavement can be factored into the analysis.

Because the program attempts to include all costs associated with a strategy, a large number of inputs are required not only pertaining to material properties but including such difficult to determine factors as traffic growth, vehicle operating costs, emissions, accidents, etc. In every case the program will attempt to provide reasonable default values that can be overridden by the user when better data is available.



Once you've logged in, you can choose from a list of programs to train on. You can also access extensive online literature about the programs from this screen.



CRCP-9 & CRCP-10

The CRCP programs assist the user in evaluating a proposed design for continuously reinforced concrete pavement. Inputs include design parameters, environmental and traffic loading stresses, and material properties. The program predicts crack spacing, crack width, steel stress, and rate of punchout development.



CRCP9 and CRCP10 differ only in that CRCP10 takes into account dynamic wheel loading. If dynamic loading is not a factor, CRCP9 is recommended since it is slightly less complicated to use and gives the same results.

JRCP-6

The *JRCP Version 6.0* software is an analysis program for jointed reinforced pavement. JRCP predicts the stresses on a user-defined pavement. The user enters data such as reinforcement type, amount of reinforcement, environmental conditions, and concrete properties. *JRCP-6* may also be used to predict the stresses on jointed pavement that has no reinforcement. To do this, simply enter a small number (0.01, for example) for the **Percent Reinforcement** option on Screen 3 of the JRCP inputs.



Pave Pro

The **PavePro** system was developed to assist in the management of temperature in newly-placed Portland cement concrete pavements. Given general, mix design, materials, environmental, and construction inputs, the system can predict the temperature within and below a concrete pavement slab. The system calculates and plots the average concrete temperature over the first 48 hours, and the temperature profile through the concrete slab and into the subbase during the first 36 hours after placement.

